Claims

What is claimed:

- In a digital cable-system environment, an apparatus for inserting one or more local signals during a delay period associated with the execution of a channel change command, the apparatus comprising:
 - a memory for storing one or more local signals;
 - a processor for recognizing the delay period associated with the channel change command; and
 - a signal insertion module, coupled to the memory and the processor, for retrieving a local signal from the memory and for inserting the local signal in the delay period.
 - The apparatus of claim 1, wherein the local signal is 2. a targeted advertisement.
 - The apparatus of claim 1, wherein the local signal is an audio signal.

<u>__</u>10

in property of the first of the

The apparatus of claim 1, wherein the local signal is a graphics signal.

20

5. The apparatus of claim 1, further comprising a demultiplexer for recalculating a new program stream based on the channel change command.

5

6. In a digital cable-system environment, a method for inserting one or more local signals during a delay period associated with the execution of a channel change command, the method comprising:

recognizing the delay period associated with the execution of the channel change command;

transmitting a request for a local signal, wherein the local signals are stored in memory;

receiving a local signal in response to the transmitted request; and

inserting the local signal during the delay period.

7. The method of claim 6, wherein the local signal is a targeted advertisement.

20

- 8. The method of claim 6, wherein the local signal is an audio signal.
- The method of claim 6, wherein the local signal is a
 graphics signal.
 - 10. The method of claim 6, wherein the local signal is an HTML page, either locally stored or received real-time from any source.
 - 11. The method of claim 10, wherein the local signal is a Java application.
 - 12. The method of claim 6, wherein the local signal is an analog TV channel.
 - 13. The method of claim 6, wherein the local signal is a locally stored MPEG stream.

14. The method of claim 6, further comprising a demultiplexer for recalculating a new program stream based on a channel change command.